

Triplex Cable Surround Data Sheet

Manufactured as standard in a LSF Zero Halogen polymeric material. Used within a single cable cleat to secure triplex cable (three single core cables which are spirally twisted together), it overcomes the twist in the cable so allowing the cable to be cleated at any point along it's length.

UK Patent GB 238 9970



Part No	Triplex Cable Range		Depth mm	Weight g
	Min dia. Mm	Max dia. Mm		
SFT26	24	28	62	67.3
SFT31	28	34	62	87.0
SFT36	33	39	62	113.4
SFT43	39	47	62	140.0
SFT51	47	55	62	212.3

This product has been tested in line with EN 50368.

Maximum short circuit test level (within 2F Clamps), 76kA at 600mm cleat spacing

See page 2 for Cable Cleat selection details

Cable Cleat Selection Detail for Cleats to be used with the SFT Surround for Triplex Cable

Cable Core Outside	SFT Outside Diameter	Adaptor Type	Cleat Vulcan +	Cleat Emperor	2F Clamp
24	56	SFT26	VRT+03	ES51-59	9
25	58	SFT26	VRT+03	ES51-59	10
26	59	SFT26	VRT+03	ES58-66	10
27	61	SFT26	VRT+04	ES58-66	10
28	63	SFT26	VRT+04	ES58-66	10
28	66	SFT31	VRT+04	ES65-73	11
29	68	SFT31	VRT+04	ES65-73	11
30	70	SFT31	VRT+05	ES65-73	11
31	72	SFT31	VRT+05	ES65-73	1200
32	73.5	SFT31	VRT+05	ES73-85	1200
33	75	SFT31	VRT+06	ES73-85	1200
34	77	SFT31	VRT+06	ES73-85	1201
33	77	SFT36	VRT+07	ES73-85	1201
34	79	SFT36	VRT+07	ES73-85	1201
35	80	SFT36	VRT+07	ES73-85	1201
36	83	SFT36	VRT+07	ES73-85	1201
37	85	SFT36	VRT+07	ES84-94	1202
38	86	SFT36	VRT+07	ES84-94	1202
39	87	SFT36	VRT+07	ES84-94	1202
39	92	SFT43	VRT+08	ES84-94	131
40	94	SFT43	VRT+08	ES94-118	131
41	96	SFT43	VRT+08	ES94-118	131
42	98	SFT43	VRT+09	ES94-118	132
43	100	SFT43	VRT+09	ES94-118	132
44	101	SFT43	VRT+09	ES94-118	132
45	103	SFT43	VRT+10	ES94-118	132
46	104.5	SFT43	VRT+10	ES94-118	132
47	106	SFT43	VRT+10	ES94-118	141
47	107	SFT51	VRT+12	ES94-118	141
48	109	SFT51	VRT+12	ES94-118	141
49	111	SFT51	VRT+12	ES94-118	141
50	113.5	SFT51	VRT+12	ES94-118	142
51	115.5	SFT51	VRT+12	ES94-118	142
52	118	SFT51	VRT+12	ES94-118	142
53	120	SFT51	VRT+12	ES118-130	142
54	122.5	SFT51	VRT+12	ES118-130	151
55	125	SFT51	VRT+12	ES118-130	151