

SHOES FOR PROFESSIONALS



HAIX®-Climate-System



Heel bend



RTC with countersunk seams

Upper Material: Waterproof leather, hydrophobic, breathable (5,0 mg/cm²/h), 2.5 – 2.7 mm thick

Inner lining: GORE-TEX® Laminat Technology 4-layer GORE-TEX® laminate, waterproof and breathable. Highly abrasion-resistant lining with fleece midlayer. Optimized- climate comfort for all year seasons and excessive use. Increased chemical protection.

Plastic Insole: Dimensionally stable, torsion-proof, avoids punctual pressure (e.g. of stones)

Footbed: Insole, anatomically formed, exchangeable, washable, very good moisture absorption, dries quickly

Protective Toe Cap: Anatomically formed protective toe cap

Sole: Stable rubber/PU sole with a robust terrain tread, wear resistant and non-slip traction. The low-weight PU, impact-absorbing wedge in the heel area cushions every step and affords good bending comfort. The manually-applied rubber sidewall gives this sole optimal side stability. Compliant with EN ISO 20345:2004

HAIX®-Climate-System: Climate System with Micro-Dry lining at top of leg

Others: Lacing system with eyelets permitting smooth movement, clamps and hooks, integrated heel bend, no side seams, rubber toe cap

CLIMBER

Art.-Nr. 603013

CE EN 345 SB HI CI WR

Leather thickness 2,5 – 2,7 mm, waterproof and breathable with GORE-TEX® Laminat Technology, HAIX®-Climate-System, Leg height 22 cm

Available sizes EU 38 – 47, Extra large sizes EU 48



UK	3	3 1/2	4	4 1/2	5	5 1/2	6	6 1/2	7	7 1/2	8	8 1/2	9	9 1/2	10	10 1/2	11	11 1/2	12	12 1/2	13	13 1/2	14
EU	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50							
US	4	4 1/2	5	5 1/2	6	6 1/2	7	7 1/2	8	8 1/2	9	9 1/2	10	10 1/2	11	11 1/2	12	12 1/2	13	13 1/2	14	14 1/2	15



HAIX®-Schuhe
Produktions- und Vertriebs GmbH



CABLE JOINTS, CABLE TERMINATIONS, CABLE GLANDS, CABLE CLEATS
FEEDER PILLARS, FUSE LINKS, ARC FLASH, CABLE ROLLERS, CUT-OUTS

11KV 33KV CABLE JOINTS & CABLE TERMINATIONS

FURSE EARTHING

www.cablejoints.co.uk

Thorne and Derrick UK

Tel 0044 191 490 1547 Fax 0044 191 477 5371

Tel 0044 117 977 4647 Fax 0044 117 9775582